

PRODUCT SPECIFICATIONS FOR D6T

Engine Model	Cat C9
Power - Net	149 kW
Emissions	Brazil MAR-1, equivalent to U.S. EPA Tier 3/EU Stage IIIA
Net Power - ISO 9249	138 kW
Note (1)	Engine ratings apply at 1,850 rpm. Net power advertised is the power available at the flywheel when engine is equipped with a fan at maximum speed, air cleaner, muffler and alternator. Advertised power is tested per the specified standard in effect at the time of manufacture.
Net Power - ISO 9249	149 kW
Note (1)	Engine ratings apply at 1,850 rpm. Net power advertised is the power available at the flywheel when engine is equipped with a fan at maximum speed, air cleaner, muffler and alternator. Advertised power is tested per the specified standard in effect at the time of manufacture.
Fuel Tank	424 l
Operating Weight	20449 kg
Operating Weight - STD A-Blade	19969 kg
Operating Weight - STD	19429 kg

SU-Blade	
Operating Weight - XL A-Blade	20661 kg
Operating Weight - XL SU-Blade	20449 kg
Operating Weight - LGP S-Blade	22039 kg
Note (1)	Operating Weight includes blade, lubricants, coolant, full fuel tank, standard track, ROPS/FOPS cab, drawbar and operator.

S-Blade Capacity - LGP	3.8 m ³
SU - Blade Capacity	5.6 m ³
SU XL - Capacity	5.6 m ³
A-Blade Capacity	3.9 m ³
A XL - Capacity	3.9 m ³
S-Blade Width - LGP	4063 mm
SU - Blade Width	3260 mm
SU XL - Width	3260 mm
A-Blade Width	4166 mm
A XL - Width	4500 mm

D6T STANDARD EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

POWER TRAIN

C9 diesel engine

Radiator, Aluminum Bar Plate

Air cleaner, precleaner with stratta tube dust ejector

Air filter with electronic service indicator

Aftercooler, air to air (ATAAC)

Coolant, extended life

Fan, blower, direct drive

Final drives, three planet single reduction planetary

Fuel priming pump, electric

Muffler, insulated with mitered stack

Parking brake, electronic

Prescreener

Shift management: – Automatic directional and downshift – Controlled throttle, load compensated

Starting aid, ether, automatic

Torque divider

Transmission, electronically controlled powershift 3F/3R speeds

Turbocharger, wastegate

Water separator

UNDERCARRIAGE

Cat Abrasion
Carrier rollers
Equalizer bar, heavy duty
Guards, end track guiding
Idlers, center tread, lifetime lubricated
Rollers, lifetime lubricated track
Track roller frames, tubular
Track adjusters, hydraulic
Sprocket rim segments, replaceable

ELECTRICAL

Alarm, backup
Alternator, 95 amp, brushless
Batteries, 2 maintenance free 12V (24V system), heavy duty
Converter, 12V, 10 amp with 2 outlets
Connector, diagnostic
Electric start, 24V
Horn, forward warning

OPERATOR ENVIRONMENT

Air conditioner, underhood
Armrest, adjustable
Cab, ROPS/FOPS, sound suppressed
Decelerator pedal
Differential steering control with touch shift
Electronic Monitoring System with coolant power train oil, and hydraulic oil temperature, fuel gauge, tachometer, odometer, gear indicator and diagnostic functions
Foot pads, dash
Heater
Hour meter, electronic
Hydraulic controls, pilot operated with electronic deactivation switch
Mirror, rearview
Radio ready
Seat, adjustable contour suspension
Seatbelt, retractable 76 mm (3 in)
Throttle switch, electronic
Wipers, intermittent

CAT TECHNOLOGY

Compatibility with radios and base stations from Trimble, Topcon, and Leica
Capability to install 3D grade systems from Trimble, Topcon, and Leica

OTHER STANDARD EQUIPMENT

CD ROM Parts Book
Engine enclosures, perforated
Front pull device
Guards, hinged bottom
Hood, perforated

Hydraulics, independent steering and work tool pumps

Hydraulics, load sensing, dozer lift and tilt

Oil cooler, hydraulic

Product link ready

Radiator doors, louvered, hinged, fan blast deflector

S·O·S sampling ports

Tool box

Vandalism protection for fluid compartments and battery box

D6T OPTIONAL EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

POWER TRAIN

Drains, ecology, power train

Prescreener

Grid, radiator core protector

Fan, ejector

Fan, reversible

Precleaner, turbine with screen

Precleaner, turbine without screen

Thermal shield arrangement

UNDERCARRIAGE

Undercarriage, Heavy Duty

Track pairs (Standard roller frame, 39 section): – Extreme Service (HD) 560 mm (22 in) – Extreme Service (Cat Abrasion) 560 mm (22 in) – Non-Trapezoidal (Cat Abrasion) 610 mm (24 in) – Moderate Service (HD) 560 mm (22 in) – Moderate Service (Cat Abrasion) 610 mm (24 in)

Track pairs (XL non-VPAT roller frame, 41 section): – Extreme Service (HD) 560 mm (22 in) – Extreme Service (HD) 610 mm (24 in), non-trapezoidal – Extreme Service (Cat Abrasion) 560 mm (22 in) – Extreme Service (Cat Abrasion) 610 mm (24 in), non-trapezoidal – Moderate Service (HD) 610 mm (24 in) – Extreme Service (HD) 610 mm (24 in), trapezoidal – Extreme Service (Cat Abrasion) 560 mm (22 in), center hole

HYDRAULICS

Hydraulics, ripper

STARTERS, BATTERIES AND ALTERNATORS

Alternator, 150 amp

Alternator, 95 amp, ducted

Heater, engine coolant, 120V

Batteries, heavy duty and starter

ELECTRICAL

Lights, five

Lights, seven

Lights, eleven

Lights, sweeps

Light, warning strobe

Switch, disconnect, remote mounted

OPERATOR ENVIRONMENT

Air conditioner, ROPS mounted

Canopy

Seat, vinyl

Camera, rear vision

Cab, arrangement with screens

Glass, dual pane and precleaner

Handles, heavy duty

CAT TECHNOLOGY

Security system, machine

TECHNOLOGY PRODUCTS

AccuGrade ready, cab

Blade groups with AccuGrade mounts

GUARDS

Note: Additional guarding may be required for some tractor applications

Idler seals

Heavy duty crankcase guard

Hinged radiator guard

Metal hose protection sleeve

Clamshell final drive

Final drive seals

Fuel tank guard

Precleaner

Heavy duty radiator

Hinged heavy duty radiator

Rear tractor guard

Rear screen

Forestry guarding

Moderate service track guard

Full length track guard

Full track guard

Striker bars: front and rear

Striker bar box, rear

COUNTERWEIGHTS AND DRAWBARS

Counterweight, additional

Counterweight, rear slab

Counterweight, rigid short

WINCH

Please see your Cat dealer for Winch options

MISCELLANEOUS

Paint, black hood and cylinders

Sweeps

BLADES

6SU

6S

6A

Blade, Landfill, 6SU

GROUND ENGAGING TOOLS

Ripper, multi-shank

Tooth, multi-shank ripper

Tooth, straight (1, 2 or 3)

